

Chainsaw chain oils ISO L-AC

FAM[®] TESTEROL

FAM[®] TESTEROL is high quality oil manufactured from selected solvent neutral mineral oils of naturally high viscosity index and with polycyclic aromates content not exceeding 3% and suitable additives that protect parts of chainsaws from the harmful effects of the operation and provide long and reliable operation.

ADVANTAGES

- Excellent adhesive properties enable the excellent adhesion to metal sliding surfaces of the chainsaw chains and prevent the oil splash from the chain during operation;
- It cleans chainsaw bar and chain from the contaminants such as dust, dirt or sawdust and thus assures continuous, trouble-free operation;
- Excellent antiwear and lubricating properties in high speeds protect the sharpness of the chain (teeth) for long period of time;
- Good anti-rust and anticorrosion protection properties;
- Good properties of water displacement from metal surfaces.

QUALITY LEVEL

ISO 6743-1

FAM FSP 190640

APPLICATION

FAM[®] TESTEROL is used for the lubrication of chainsaw chains.

FAM[®] TESTEROL oil has the following properties: good endurance of high pressures, excellent oil-to-chain adherence, prevention of overheating of chainsaw bar and chain in high chain speeds with minimum oil consumption.

FAM[®] TESTEROL protects sliding chain parts, guides and chain pulley from over wearing.

TYPICAL CHARACTERISTICS

	TYPICAL VALUE	METHOD
Density at 15°C, g/cm ³	0,89	SRPS EN ISO 3675
Kinematic viscosity at 40°C, mm ² /s	100,0	SRPS ISO 3104
Kinematic viscosity at 100°C, mm ² /s	11,0	SRPS ISO 3104
Flash point °C	220	SRPS EN ISO 2592
Pour point °C	-15	SRPS ISO 3016



STORAGE

Store in covered area. If stored outdoors, it is necessary to place the drums in a horizontal position to prevent the accumulation of water on the surface of the drum. Do not store at elevated temperatures or in locations exposed to direct sunlight.

All necessary instructions can be found in the product SDS. It contains the details of possible hazards, warnings and first aid measures, as well as the impact on the environment and the necessary measures for the storage and handling.

PACKING

Drums 180 kg, plastic cans 1L and 5L.

Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.



December, 2016

FABRIKA MAZIVA FAM • Jug Bogdanova 42 • 37000 Kruševac • Serbia

Tel. ++381 37 422078; 423261 • Fax. ++ 381 37 426241; 424008

www.fam.rs