

Products with volatile solvent - film: solid, flexible

FAMCORTIL[®] 111 UB

FAMCORTIL[®] 111 UB is anticorrosion covering made of high quality corrosion inhibitors, microwaxes, components for thixotropic property improvement and easily volatile organic solvents.

ADVANTAGES

- Dark, brown-metallic, dry, elastic protective film remains on protected surfaces after solvent evaporation,
- It provides protection to treated surfaces up to 5 years in conditions of indoor storage, i.e. up to 3 years outdoors.
- This film has the following characteristics: high resistance to salty and wet atmosphere, water, chipping, high elasticity, resistance to cracking and peel off.
- Protective film is not harmful to rubber and plastic.

QUALITY LEVEL

ISO-L-RM

MIL-C-16173 D/I

APPLICATION

FAMCORTIL[®] 111 UB is intended for automotive industry. It is used for the protection of internal and external floor surfaces and complete internal car-body surfaces of all types of vehicles: passenger vehicles, buses, trucks and military vehicles. It is also used for the protection of bulky metal parts and constructions which are exposed to atmospheric influences for longer period of time.

FAMCORTIL[®] 111 UB is applied to clean, degreased and dry surfaces at room temperature by spraying or by coating, at operating pressure of 6-8 bar. Applied film solidifies in 2 hours and after 14-16 hours it is completely dry and vehicle is ready to be used in all conditions. It is easily removed from coloured surfaces with petroleum solvents, gasoline...

TYPICAL CHARACTERISTICS

CHARACTERISTICS	UNITS	FAMCORTIL[®] 111 UB	METHODS
Appearance	-	Dark-brown	Visual
Flash point	°C	Min.22	SRPS EN ISO 2719
Anticorrosion protection salt spray	h	Min.600	SRPS ISO 9227
Protective film thickness	µm	Min. 150	MIL C 16173 D
Coverage	m ² /l	3-5	-



NOTES FOR SAFETY AT WORK

- Do not apply the product to the heated surfaces and near the open flame,
- When applying, take measures to protect the respiratory tract, eyes and hands

STORAGE

Store in a confined space, intended for the storage of flammable materials. Tightly closed original containers should not be stored in places exposed to direct sunlight, nor at temperatures below 5°C. All necessary instructions can be found in the Safety Data Sheet. It contains details of possible hazards, warnings and first aid measures, as well as the environmental impact and the necessary measures when storing.

PACKING

Tin pails of 4.5 and 17 kg and tin drums of 180 kg.

Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.



December, 2016

FABRIKA MAZIVA FAM • Jug Bogdanova 42 • 37000 Kruševac • Serbia
Tel. ++381 37 422078; 423261 • Fax. ++ 381 37 426241; 424008
www.fam.rs