

Lubricant for closed gear transmissions, ISO L-CKT / CKL

FAMFLUID[®] OK

FAMFLUID[®] OK: special soap thickener based lubricant that provides good EP and antiwear properties, good adhesion and corrosion protection.

ADVANTAGES

- It does not contain bitumen
- It does not contain solvents
- It does not contain lead and chlorine
- Built in are the oils with polycyclic aromatics (PCA) content up to max. 3%.

QUALITY LEVEL

ISO L-CKT / CKL

SCOPE OF APPLICATION

- Cement, rubber industry
- Mining
- Construction industry
- Non-metal industry

APPLICATION

- FAMFLUID[®] OK special lubricant is primarily intended for the lubrication with procedure from carter.
- It is applied for the lubrication of open and closed gear transmissions operating under uneven and extremely high loads.
- Temperature range of application: -20 to +120°C

TYPICAL CHARACTERISTICS

Characteristics	Units	FAMFLUID [®] OK	Methods
Colour		black	visual
Soap type/Thickener	-	Lithium soap	-
Brookfield viscosity	mPas	30000	ASTM D 2983
Flash point	°C	200	SRPS EN ISO 2592
Average wear diameter	mm	0,45	ASTM D 2266
Weld load	N	5000	ASTM D 2596
Temperature of application	°C	- 20 to + 120	



STORAGE

Store in a covered area, protected from direct influence of sun and moisture, away from the ignition source. Recommended storage temperature: - 5°C to +25°C.

All necessary instructions can be found in the product SDS. It contains the details of possible hazards, warnings and first aid measures, as well as the impact on the environment and the necessary measures for the storage and handling.

PACKING

Cans of 20 kg and tin drums of 180 kg.

Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.



December, 2016

FABRIKA MAZIVA FAM • Jug Bogdanova 42 • 37000 Kruševac • Serbia

Tel. ++381 37 422078; 423261 • Fax. ++ 381 37 426241; 424008

www.fam.rs