

Engine oils

ISO L-E

FENIX[®] EXTRA SINT SAE 10W-40

FENIX[®] EXTRA SINT SAE 10W-40 is top quality fully synthetic multigrade engine oil of new generation UHPD (Ultra High Performance Diesel) quality with reduced level of SAPS (sulphated ash, phosphorus, sulphur), recommended for the most modern highly loaded diesel engines of commercial vehicles which have built-in the exhaust after-treatment systems (EGR, DPF with or without separate filter for particles, SCR) and which meet the requirements of EURO V and EURO VI.

ADVANTAGES

- Supreme protection against wear in all conditions of engine operation;
- Extended engine life and oil change interval;
- Easy start at low temperatures;
- Excellent high temperature characteristics;
- It saves fuel, reduces costs;
- Compatible with performances of modern systems for exhaust gases purification;
- Owing to its high viscosity index and superb additive package, it provides maximum protection of the engine from wear at extremely high operating temperatures;
- Excellent detergent - dispersion properties maintain engine purity and its power;
- Extended engine life;
- Exceptional oxidation and thermal stability.

QUALITY LEVEL

ISO 6743-15

API CI-4

ACEA E6-12 / E7-12

VOLVO VDS 3

MB Approval 228.51

MTU Type 3.1

MAN M3477/M3271-1

RVI RXD; RLD/ RLD-2

Deutz DQC-IV-10-LA

Cummins CES 20076/77

MACK EO-N

APPLICATION

FENIX[®] EXTRA SINT SAE 10W-40 engine oil provides:

- Supreme protection against wear in all conditions of engine operation
- Extended oil change intervals;
- Compatibility with the environment;
- Extended engine life;
- Reduced costs;
- Extended lifetime of the exhaust after-treatment system.

FENIX[®] EXTRA SINT SAE 10W-40 is recommended for diesel engines of heavy cargo vehicles, buses and construction machines when extremely long oil change interval is required. It is formulated to provide

December, 2017

FABRIKA MAZIVA FAM • Jug Bogdanova 42 • 37000 Kruševac • Serbia

Tel. ++381 37 422078; 423261 • Fax. ++ 381 37 426241; 424008

www.fam.rs

excellent performances in vehicles with the exhaust after-treatment system (DPF/CRT - Diesel Particulate Filter/Continuously Regenerating Trap). This engine oil is also recommended in engines with selective catalytic reduction - SCR (Selective Catalytic Reduction) as well as in engines using LPG and CNG.

FENIX® EXTRA SINT SAE 10W-40 is used for recommended oil change intervals even up to 100 000 km, in conditions of highway traffic and by using good quality diesel fuel. For exact oil change intervals we recommend you to follow vehicle manufacturer instructions.

TYPICAL CHARACTERISTICS

	TYPICAL VALUE	METHOD
Density at 15°C, g/ml	0,85	SRPS EN ISO 3675
Kinematic viscosity at 40°C, mm ² /s	85	SRPS ISO 3104
Kinematic viscosity at 100°C, mm ² /s	12.5	SRPS ISO 3104
Viscosity index	150	SRPS ISO 2909
Dynamic viscosity at -25°C, mPas	6650	DIN 53018/1
Flash point, °C	220	SRPS EN ISO 2592
Pour point, °C	-45	SRPS ISO 3016
TBN, mg KOH/g	12.7	SRPS ISO 3771
Sulphated ash, %	1,0	SRPS ISO 3987

STORAGE

Store in covered area. If stored outdoors, it is necessary to place the drums in a horizontal position to prevent the accumulation of water on the surface of the drum. Do not store at elevated temperatures or in locations exposed to direct sunlight.

All necessary instructions can be found in the product SDS. It contains the details of possible hazards, warnings and first aid measures, as well as the impact on the environment and the necessary measures for the storage and handling.

PACKING

Drums 175kg, plastic containers of 10L and 5L.

Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.