

Engine oils

ISO L-E

FENIX[®] GAS OIL SAE 15W-40

FENIX[®] GAS OIL SAE 15W-40 is multigrade mineral engine oil for gasoline engines adapted for LPG, made from specially selected additives and highly refined solvent neutral base oils.

This oil is formulated to protect the engines from high temperatures that are achieved by dry combustion as a result of the use of gas fuels.

ADVANTAGES

- Excellent shear stability;
- Excellent thermal and oxidation stability;
- Reduces lacquering, the formation of sludge and other deposits in the engine;
- Good detergent-dispersing properties;
- Improved protection against wear and corrosion of engine parts;
- Easy engine start and application at all seasons;
- It prevents piston ring seizure;
- It keeps the pistons clean and protects the engine against rust and corrosion;
- Low volatility.

QUALITY LEVEL

ISO 6743-15

ACEA A3/B4

API SL/ CF

VW 501.01/505.00

MB 229.1

APPLICATION

FENIX[®] GAS OIL SAE 15W-40 is high quality and highly reliable engine oil specially formulated for use in passenger cars with gasoline engines that are adapted to use also LPG. This engine oil is optimum lubricant for gasoline engines, and therefore its constant and regular use protects engine against wear.

By constant use of this engine oil in cars with gasoline engines using LPG, the engine oil change interval can be extended up to 50%.

TYPICAL CHARACTERISTICS

	TYPICAL VALUE	METHOD
Density at 15°C, g/ml	0,88	SRPS EN ISO 3675
Kinematic viscosity at 40°C, mm ² /s	104	SRPS ISO 3104
Kinematic viscosity at 100°C, mm ² /s	14	SRPS ISO 3104
Dynamic viscosity at -20°C, mPas	6850	DIN 53018/1
Viscosity index	135	SRPS ISO 2909
Flash point, °C	230	SRPS EN ISO 2592
Pour point, °C	-30	SRPS ISO 3016
TBN, mg KOH/g	6,8	SRPS ISO 3771



STORAGE

Store in covered area. If stored outdoors, it is necessary to place the drums in a horizontal position to prevent the accumulation of water on the surface of the drum. Do not store at elevated temperatures or in locations exposed to direct sunlight.

All necessary instructions can be found in the product SDS. It contains the details of possible hazards, warnings and first aid measures, as well as the impact on the environment and the necessary measures for the storage and handling.

PACKING

Drums 175kg, plastic containers of 1L and 4L.

Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.



December, 2016

FABRIKA MAZIVA FAM • Jug Bogdanova 42 • 37000 Kruševac • Serbia

Tel. ++381 37 422078; 423261 • Fax. ++ 381 37 426241; 424008

www.fam.rs