

Engine oils

ISO L-E

FENIX[®] SUPER SAE 15W-40

FENIX[®] SUPER SAE 15W-40 is highly efficient engine oil made from specially selected additives and high quality solvent neutral base oils. It provides good detergent dispersion properties, efficient engine anti-wear protection and maximum engine purity.

ADVANTAGES

- High alkaline reserve level;
- Excellent shear stability;
- Exceptional thermal and oxidation stability;
- Improved protection against wear and corrosion of engine parts;
- Easy engine start and application at all seasons;
- Improved cold start compared to monograde engine oils;
- Low volatility.

QUALITY LEVEL

ISO 6743-15	RLD/RLD-2
API CH-4/CF-4/CF/SJ	VOLVO VDS-3
ACEA E7-16	Cummins CES 20076/77
MAN 3275	Detroit Diesel DDC 93K215
MTU Type 2	MACK EO-M Plus/ EO-N
MB 228.3	CAT ECF-1-a

APPLICATION

FENIX[®] SUPER SAE 15W-40 is highly efficient engine oil of the widest range of application designed to lubricate modern four-stroke gasoline engines with and without catalysts and diesel engines of passenger and cargo vehicles as well as diesel engines of commercial vehicles operating in moderately difficult conditions of exploitation including turbocharger and intercooler engines, multivalve distributor engines, with and without catalyst, as well as for engines with computer controlled fuel injection. It is suitable for use in EURO 3 engines.

TYPICAL CHARACTERISTICS

	TYPICAL VALUE	METHOD
Density at 15°C, g/ml	0,88	SRPS EN ISO 3675
Kinematic viscosity at 40°C, mm ² /s	105	SRPS ISO 3104
Kinematic viscosity at 100°C, mm ² /s	14	SRPS ISO 3104
Viscosity index	135	SRPS ISO 2909
Dynamic viscosity at -20°C, mPas	6900	DIN 53018/1
Flash point, °C	220	SRPS EN ISO 2592
Pour point, °C	-30	SRPS ISO 3016
TBN, mg KOH/g	9,5	SRPS ISO 3771
Sulphated ash, %	1,3	SRPS ISO 3987

December, 2016

FABRIKA MAZIVA FAM • Jug Bogdanova 42 • 37000 Kruševac • Serbia

Tel. ++381 37 422078; 423261 • Fax. ++ 381 37 426241; 424008

www.fam.rs

STORAGE

Store in covered area. If stored outdoors, it is necessary to place the drums in a horizontal position to prevent the accumulation of water on the surface of the drum. Do not store at elevated temperatures or in locations exposed to direct sunlight.

All necessary instructions can be found in the product SDS. It contains the details of possible hazards, warnings and first aid measures, as well as the impact on the environment and the necessary measures for the storage and handling.

PACKING

Drums 175kg, plastic containers of 4L and 1L.

Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.

